

PRODUCT SPECIFICATIONS

HEAT KITS

HEAT KIT ELECTRICAL DATA

MODEL NO.	NOMINAL kW	HEATER AMPERAGE	MINIMUM AMPACITY	MAXIMUM OVERCURRENT PROTECTION	MULTIPLE SUPPLY CIRCUIT			
					MINIMUM		MAXIMUM	
					208/240V			
					1	2	1	2
HK05-1*	4.75	17.2/19.8	22/25	30/30				
HK08-1*	7.00	25.3/29.2	32/37	60/60				
HK10-1*	9.50	34.4/39.6	45/50	60/60				
HK10-3	9.50	20.7/23.6	26/30	30/30				
HK15-1	14.25	51.5/59.4	65/75	90/90	22/25	43/50	30/30	60/60
HK15-3*	15.00	31.7/36.2	40/46	50/50				
HK15-4**	15.00	18.1	23	30				
HK20-1*	19.00	68.7/79.2	86/99	120/120	43/50	43/50	60/60	60/60
HK20-3	19.60	41.4/47.2	52/59	60/60				
HK20-4**	19.60	23.6	30	30				

* Circuit Breaker Models

** Ratings at 480 VAC, Phase 3

NOTE: Ratings are at 208/240 VAC unless otherwise noted.

kW Correction Factor

Supply Voltage	240	230	220	210	208
Correction Factor	1	0.93	0.85	0.78	0.76
(Multiply the 240 VAC capacity by factors)					

NOTE: SPECIFICATIONS AND PERFORMANCE DATA LISTED HEREIN ARE SUBJECT TO CHANGE WITHOUT NOTICE

HK Heat Kit Selection Charts

	PC / PCK / PCKJ											
	024-1	030-1	036-1	036-3	042-1	042-3	048-1	048-3	048-4	060-1	060-3	060-4
HK05-X	X	X	X	X	X	X	X	X	X	X	X	X
HK08-X	X	X	X	X	X	X	X	X	X	X	X	X
HK10-X	X	X	X	X	X	X	X	X	X	X	X	X
HK15-X		X	X	X	X	X	X	X	X	X	X	X
HK20-X			X	X	X	X	X	X	X	X	X	X

	PH / PHK / PHKJ										
	024-1	030-1	036-1	036-3	042-1	048-1	048-3	048-4	060-1	060-3	
HK05-X	X	X	X	X	X	X	X	X	X	X	
HK08-X	X	X	X	X	X	X	X	X	X	X	
HK10-X	X	X	X	X	X	X	X	X	X	X	
HK15-X		X	X	X	X	X	X	X	X	X	
HK20-X			X	X	X	X	X	X	X	X	

Note: X – 1,3 & 4 are electrical designators

1 – 208/240 V, 1 PH

3 – 208/240 V, 3 PH

4 – 480 V, 3 PH